

767 Chapman Lake Drive - Warsaw, Indiana 46582

Product Data Sheet

Product: ACLLPA02NA2 Description: 2% Processing Aid PEC

<u>Product Highlights:</u> Reduces melt fracture

Increases machine thruputs Savings in raw material costs

Carrier Resin Data

Туре	<u>Units</u>	<u>Value</u> LLDPE	<u>Method</u>	
Melt Flow	g/10min	2.0	ASTM D1238	
Density	g/cm ³	0.924	ASTM D792	

Concentrate Data

Additive Loading	<u>Units</u> %	<u>Value</u> 2.0	<u>Method</u> internal	
Melt Flow	g/10min	3.0	ASTM D1238	
Pellet Weight	Pellets/gm	60	internal	

Regulatory Data

regulatory Data	
<u>FDA</u>	The components in this product comply with the following sections of Title 21, Code of Federal Regulations (21CFR): 174.5 177.1520
<u>CONEG</u>	The components of this product are compliant with the current requirements issued by the Coalition of North Eastern Governors (CONEG) requiring less than 100 PPM total in the final product packaging.

The above information is believed to be accurate and reliable. Because conditions of use are beyond our control, we make no warranties, expressed or implied, and specifically exclude any and all warranties of merchantability and fitness for a particular purpose. This material is sold with the express understanding that our customers will conduct their own test to determine the suitability of the material for their particular application.