

767 Chapman Lake Drive - Warsaw, Indiana 46582

Product Data Sheet

|--|

<u>Product Highlights:</u> Stabilizes polymer against UV degradation

High temperature stability Effective in thick sections

Carrier Resin Data

| Туре | <u>Units</u> | <u>Value</u> LLDPE | <u>Method</u> |
|-----------|-------------------|-----------------------|---------------|
| Melt Flow | g/10min | 20.0 | ASTM D1238 |
| Density | g/cm ³ | 0.924 | ASTM D792 |

Concentrate Data

| Additive Loading | <u>Units</u> % | <u>Value</u> 10.0 | <u>Method</u> internal | |
|------------------|-------------------|----------------------|---------------------------|--|
| Melt Flow | g/10min | 23.0 | ASTM D1238 | |
| Pellet Weight | Pellets/gm | 60 | internal | |

Regulatory Data

| <u>FDA</u> | The components in this product comply with the following sections of Title 21, Code of Federal Regulations (21CFR): |
|--------------|---|
| | 174.5 178.2010 177.1520 |
| <u>CONEG</u> | The components of this product are compliant with the current requirements issued by the Coalition of North Eastern Governors (CONEG) requiring less than 100 PPM total in the final product packaging. |

The above information is believed to be accurate and reliable. Because conditions of use are beyond our control, we make no warranties, expressed or implied, and specifically exclude any and all warranties of merchantability and fitness for a particular purpose. This material is sold with the express understanding that our customers will conduct their own test to determine the suitability of the material for their particular application.