

767 Chapman Lake Drive - Warsaw, IN 46852

MATERIAL SAFETY DATA SHEET

Section 1 Product Identification

Product Code:CCEVCB50BK1Date Prepared:Aug. 17, 2007Description:Black EVA Concentrate574-527-9957Aug. 17, 2007

Section 2 Composition; Information on Hazardous Ingredients

| Chemical Common Name | CAS Number | OSHA PEL | ACGIH TLV | OTHER | Percent mm Hg @ Temp | NTP | IARC | OSHA | PROP 65 | TSCA | 313 |
|-------------------------|---------------|-----------|-----------|-------|----------------------------|-----|------|------|------------|------|-----|
| Carbon Black | 1333-86-4 | 3.5MG/M3* | 3.5MG/M3* | | | Ν | Y | N | Y | Y | N |

* Indicates dust or mist

Section 3 Hazards Identification

Inhalation Signs and Symptoms of Exposure

May cause temporary discomfort to upper respiratory tract due to mechanical irritation when exposures are above the occupational exposure limit.

Skin and Eye Contact Signs and Symptoms of Exposure

May cause irritation to skin-may cause redness or swelling to eyes in certain individuals. Skin Absorption Signs and Symptoms of Exposure

None likely to occur

Ingestion Signs and Symptoms of Exposure

None known

Carcinogenicity

Carbon black has been evaluated by IARC as possibly carcinogenic to humans. (Group 2B) NIOSH Recommends that only carbon black with PAH>0.1% be suspected carcinogens. The ACGIH classifies carbon black as A4, not classifiable as a human carcinogen. Modern production and quality control procedures are able to maintain adsorbed PAH levels to less than 0.1% in carbon black. Carbon Black (airborn, unbound particles of respirable size) is a California Proposition 65 listed substance.

Health Hazards (Both Acute and Chronic)

Product may cause skin irritation. Carbon Black can cause nose, throat, and lung irritation. Can cause chest pain, difficult breathing, headache, and possibly lung damage. Precautions against breathing dust should be followed when handling and working with material containing carbon black.

Section 4 First Aid Measures

First Aid for Skin

Molten Resins: Cool under running stream of water. Do not attempt to remove from skin. Get medical attention.

First Aid for Eyes

This product is a solid. If in eye, remove as one would any foreign object.

First Aid for Inhalation and Ingestion

In case of adverse exposure to vapors and/or aerosols formed at elevated temperatures, immediately remove victim from exposure. Administer artificial respiration if breathing stopped. Get medical attention. Ingestion not anticipated.

Section 5 Fire Fighting Measures

| Foam | Alcohol Foam | CO2 | Dry Chemical | Water Fog | Other | Flash Point | Flash Method |
|------|--------------|-----|--------------|-----------|-------|-------------|--------------|
| YES | YES | YES | YES | YES | NO | | |

Special Firefighting Procedure

Standard procedures for class A fires

Unusual Fire and Explosion Hazards

Product as shipped is not a flammable dust. However, it can be a flammable dust when fines less than 200 mesh are suspended in air.

Section 6 Accidental Release Measures

Accidental Release Measures Sweep up spilled material for use or disposal

Section 7 Handling and Storage

Handling and Storage

Keep away from sparks and open flame. This product may react with strong oxidizing agents and should not be stored near such materials. Store in a sprinklered warehouse.

Ventilation (Local Exhaust, Mechanical, Special, Other)

Recommended over extruders Other Precautions

Use local ventilation

Section 8 Exposure Controls, Personal Protection

Respiratory Protection

Appropriate respirator selected and used in accordance with OSHA Subpart 1 (29 CFR 1910.134) required when exposure to airborne contaminant is likely to exceed limits for nuisance dusts.

<u>Ventilation</u> Recommended over extruders <u>Protective Gloves</u> Recommended <u>Eye Protection</u> Safety glasses with side shields recommended <u>Other Protective Clothing or Equipment</u> Use local ventilation <u>Work/Hygienic Practices</u> Use good industrial hygiene practices

Section 9 Physical and Chemical Properties

| Boiling Range | Vapor Density | Evaporation Rate | Soulable | Tech Shipping Name |
|---------------|------------------|-------------------|------------|--------------------|
| N/A | Lighter than Air | Slower than Ether | Negligible | |

Section 10 Stability and Reactivity

Stability Stable <u>Hazardous Polymerization</u> Will not occur <u>Incompatibility (Materials to Avoid):</u> Strong oxidizing agents <u>Hazardous Decomposition or by products</u> None known

Section 11 Toxicological Information

Ingestion

Please refer to section three for any available information on potential health effects. None expected from the pellet form.

<u>Skin</u>

Please refer to section three for any available information on potential health effects.

Eye

Please refer to section three for any available information on potential health effects.

Inhalation

Negligible hazard at ambient temperature (0-100 Deg. F). Vapors and aerosols may be formed at elevated temperatures.

Section 12 Ecological Information

Ecological Information

Plastic pellets are defined by US EPA under the Clean Water Act (40CFR 122.26) as a "SIGNIFICANT MATERIAL" which may require a storm water permit.

Section 13 Disposal Considerations

Waste Disposal

See 40 CFR 261. Dispose in accordance with local, state, and federal regulations. State or local hazardous waste regulations may apply if different from the federal.

Section 14 Transportation Information

Technical Shipping Name UN NA Number Freight Class Bulk Freight Class Package Dot Label Dot Placard Dot Shipping Name Dot Hazard

Section 15 Technical Information

| Chemical Common Name | CAS Number | OSHA PEL | ACGIH TLV | OTHER | % | mm Hg @ Temp | NTP | IARC | OSHA | PROP 65 | TSCA | 313 |
|-------------------------|---------------|-----------|-----------|-------|---|-----------------|-----|------|------|------------|------|-----|
| Carbon Black | 1333-86-4 | 3.5MG/M3* | 3.5MG/M3* | | | N | Y | N | Y | Y | N | |
| | | | | | | | | | | | | |

Section 16 Other Information

Other Information

The information contained herein is believed to be correct and was obtained from sources believed by Rainmaker Polymers to be accurate. However, no guarantee or warranty of any kind expressed or implied is made with respect to the information contained here.